

# GMW-200

## Wired/Wireless Gooseneck Microphone

### General Features

- Cardioid gooseneck microphone included.
- Powered by 2 x AA batteries.
- Push-To-Talk and Locked-To-Talk buttons.
- Strong zinc die-cast metal base with non glare black finish.
- Offers another hands free choice.
- Operates with existing models of CHIAYO UHF 100-channel wireless receivers and modules.

### Specifications

Model	GMW-200
Frequency range	UHF 600-900MHz
Bandwidth	25MHz
Switchable frequencies	100
RF output power	35mW**
Spurious emission	>60dB below carrier
Dynamic range	>110dB
Display screen	LCD
T.H.D.	<0.5%
Battery usde	AA x 2
Operating time	about 12 hours (Alkaline)
Peak deviation	±40KHz
Antenna	built in
Impedance	680Ω
Sensitivity	-50dB ±3dB
Max SPL	100dB for 1% T.H.D
Power requirement	6V phantom power
Dimension (mm)	50(H) x 111(W) x 148(D)
Base weight (g)	645
**Matched receivers	QR-4000U(S), SDR-7200, SDR-8200
**Matched receiver modules	SDR-6200m
**Matched portable PA systems	all CHIAYO PA systems with 100-channel receiver module

