

## MM-202 Gooseneck Microphone

### Key Features

- Ultra slim profile design for podiums, pulpit and lectern applications.
- Proprietary microphone mount design allows 110° up/down and 300° left/right angle adjustments.
- Shock isolation mount design minimizes handling and vibration noise.
- Multi-layered microphone grill minimizes pop noise.
- Can be connected to MJ-53 Condenser Microphone Adaptor and provides with 48V phantom power and used as a desktop gooseneck microphone.
- Unmatched high fidelity sound reproduction.

### Related

<b>ACT-7T</b>	Bodypack Transmitter
<b>ACT-30T</b>	Bodypack Transmitter
<b>ACT-50T</b>	Bodypack Transmitter
<b>ACT-70T</b>	Wideband Bodypack Transmitter
<b>ACT-80T</b>	Wideband Digital Miniature Bodypack Transmitter
<b>BC-100</b>	Wireless Boundary Microphone
<b>MD-101</b>	Bodypack Transmitter Holder Base

### Technical Specifications

Capsule Module	10mm $\emptyset$ Uni-directional condenser microphone
Frequency Response	50Hz~18kHz
Sensitivity	-46dBV $\pm$ 3dBV/Pa (0dB=1V/Pa)
Maximum SPL	142dB (Typical, 1%THD)
Plug	TA4F 4-pin Connector
Length	470mm / 18.5"
Color	Black
Weight	Approx. 36g / 1.3oz

