



QuickFit Ceiling Speakers

Revision 1

QuickFit Dual Cone Series

The QuickFit dual cone series QF5CS, QF6CS, QF6WRC, QF8CS and QF8CSB provide cost effective solutions for a myriad of commercial audio applications such as education, shopping centres, common areas, RSLs, clubs, restaurants, fire evacuation systems and many more.

For water resistant applications the QF6WRC is the perfect fit. With an IP55 Rating, the QF6WRC features an ABS sealed back can and an aluminium powder coated grill. The QF6WRC is suitable for shower blocks, toilets, swimming pools and other wet areas.



QuickFit Coaxial Series

For installations where SPL and intelligibility are paramount the QuickFit coaxial series of ceiling speakers are sure to satisfy. These two-way coaxial speakers feature a high powered driver and frameless magnetic grill design. The sleek grill design is sure to please end users, consultants and architects alike. The magnetic system allows easy removal of the grill, enabling quick installation. A black grill for each model can also be purchased separately as an accessory.

The QuickFit coaxial series QFC5CS, QFC6CS and QFC8CS are recommended for function rooms, school halls, retail spaces, boardrooms, places of worship, RSLs, clubs, pubs, Restaurants and many other commercial applications.



QuickFit Premium Coaxial Series

When you need more power and solid bass response the QuickFit premium coaxial series of ceiling speakers are sure to exceed expectations. This premium series features two-way coaxial drivers with frameless magnetic grills and sealed back-cans. The magnetic grill system allows easy removal of the grill for tapping changes and quick installation. If you require a black ceiling speaker it's as easy as changing the grill. A black grill for each model can be purchased separately as an accessory.

Ported through the front baffle, bass response is improved and ensures detailed bass definition. The back-can on each model provides isolation in the ceiling space ensuring spill in the ceiling cavity is kept to a minimum.

The QuickFit QF20CS, QF60CS and QF80CS products are recommended for pubs, clubs, bars, retail spaces, function rooms, boardrooms and many other commercial spaces requiring a premium high powered ceiling speaker solution.



A complete range
for every application

QuickFit Dual Cone Series

Specifications	QF5CS	QF6CS	QF6WRC	QF8CS	QF8CSB
Dual Cone Driver	5 inch	6 inch	6 inch	8 inch	8 inch
Power Taps @ 100v	0.75, 1.5, 3, 6 watts	1.25, 2.5, 5, 10 watts	1, 3, 6, 9, 12 watts 12w @ 8 Ohms	1.87, 3.75, 7.5, 15 watts	1.87, 3.75, 7.5, 15 watts
Power Taps @ 70v	0.38, 0.75, 1.5, 3 watts	0.62, 1.25, 2.5, 5 watts	0.5, 1, 3, 4.5, 6 watts 12w @ 8 Ohms	0.93, 1.87, 3.75, 7.5 watts	0.93, 1.87, 3.75, 7.5 watts
Sensitivity (1W/1M)	88dB	89dB	92dB	90dB	90dB
Frequency Response	80-20 KHz	80-20 KHz	150-20 KHz	80-20 KHz	80-20 KHz
Dispersion Degrees @ 1Khz	100	100	110	100	100
Baffle and Grill Colour	White	White	White	White	Black
Weight	0.5 Kg	0.9 Kg	1.7 Kg	1.4 Kg	1.4 Kg
Dimensions	215 x 75 mm	240 x 78 mm	238 x 138 mm	280 x 80 mm	280 x 80 mm
Cutout Dimension	180 mm	208 mm	209 mm	245 mm	245 mm
Evac Capacitor 2.2uF	YES	YES	YES	YES	YES
IEC 529 IP55 Rated	NO	NO	YES	NO	NO

QuickFit Coaxial Series

Specifications	QFC5CS	QFC6CS	QFC8CS
Coaxial 2 Way Driver	5 Inch & 25 mm	6 Inch & 25 mm	8 Inch & 25 mm
Power Taps @ 100v	1.25, 2.5, 5, 10 watts	2.5, 5, 10, 20 watts	3.75, 7.5, 15, 30 watts
Power Taps @ 70v	0.65, 1.25, 2.5, 5 watts	1.25, 2.5, 5, 10 watts	1.87, 3.75, 7.5, 15 watts
Sensitivity (1W/1M)	91dB	92dB	94dB
Frequency Response	80-20 KHz	70-20 KHz	60-20 KHz
Dispersion Degrees @ 1Khz	100	100	100
Grill Colour	White	White	White
Weight	0.9 Kg	1.2 Kg	1.6 Kg
Dimensions	205 x 72 mm	232 x 90 mm	282 x 85 mm
Cutout Dimension	178 mm	208 mm	248 mm
Evac Capacitor 2.2uF	YES	YES	YES
Black Grill Accessory	QFC5GRILLB	QFC6GRILLB	QFC8GRILLB

QuickFit Premium Coaxial Series

Specifications	QF20CS	QF60CS	QF80CS
Coaxial 2 Way Driver	4 inch & 20mm	6.5 inch & 20mm	8 inch & 20mm
Power Taps @ 100v	20, 10, 5, 2.5 watts	60, 30, 15 watts	80, 40, 20 watts
Power Taps @ 70v	10, 5, 2.5, 1.75 watts	60, 30, 15, 7.5 watts	80, 40, 20, 10 watts
LowZ Nominal Impedance	16 Ohms	16 Ohms	16 Ohms
Max Power Handling	30 watts @ 16 Ohms	60 watts @ 16 Ohms	80 watts @ 16ohms
Sensitivity (1W/1M)	89dB	90dB	90dB
Frequency Response	110-20 KHz	85-20 KHz	50-20 KHz
Dispersion Degrees @ 1KHz	130	130	110
Grill Colour	White	White	White
Weight	2.15 Kg	3.7 Kg	5.65 Kg
Dimensions	218 x 125 mm	257 x 195 mm	308 x 244 mm
Cutout Dimension	182 mm	221 mm	272 mm
Evac Capacitor 2.2uF	NO	NO	NO
Tile Bridge Included	NO	YES	YES
Black Grill Accessory	QF20CSGRILLB	QF60CSGRILLB	QF80CSGRILLB



ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde St, Silverwater NSW 2128 Australia.

Website: www.australianmonitor.com.au

International enquiries email: customersupport@australianmonitor.com.au

ABN 35 007 573 417

