

120W Mixer Amplifier



TECHNICAL SPECIFICATIONS

SPECIFICATION

Rated Power	120W
Speaker Outputs	100V or 70V & 4 Ohms - 8 Ohms-16 Ohms
Connector	Mic1 input by Unbalanced Jack Mic2 Balance XLR Socket Line 1-2 inputs by RCA: Line output by RCA
Attenuation	Microphone 1-2, Line 1-2 and Mp3/FM, bass/treble and master
MIC1 - 2 input Sensitivity	5mV
AUX1 & 2 input Sensitivity	350mV
EMC input Sensitivity MIC	350mV
MIC Frequency response	180Hz - 10kHz (+- 3dB)
AUX Frequency response	70Hz -16Hz (+- 3dB)
Noise	< 5mV (4 Ohm load output terminal)
THD	< 1% 1KHz
Protection	Short Circuit, Clip Overload and high Temp protection
Treble adjustment	10dB (+-2)
Bass adjustment	10dB (+ -2)
Rated Power Supply	AC-110-220V
Rated output voltage	120W/4 Ohm, AC220V
Priority	EMC>MIC1>Other
Dimensions	247 x 198 x 66mm
Packaging Size	343 x 302 x 121mm
Net Weight	2.6Kg
Class	D

