

Product Guide

C 0376 Professional Desk Paging Microphone 5 Pin DIN

C 0377 Professional Desk Paging Microphone 3 Pin XLR

C 0379 Professional Desk Paging Microphone 5 Pin XLR

Professional Desktop Paging Microphones




Overview

This desk microphone has a tapered low frequency response for articulate speech reproduction and enhanced clarity. Fitted with a 2 metre lead. The 5 pin XLR and 5 pin DIN type connectors include a PTT mute switching pair. The PTT switch features both momentary and lock-on.


Key Features

- ✓ All metal casing, gooseneck and grille.
- ✓ PTT pair for muting auxiliary inputs. (5 pin models only)
- ✓ Heavy duty flexible steel gooseneck.
- ✓ Momentary and lock-on on mic switch positions.
- ✓ Ideal for supermarkets, fast food restaurants etc.


Wiring Configuration



**C 0376 5 Pin DIN
Wiring Diagram**



**C 0377 3 Pin XLR
Wiring Diagram**



**C 0379 5 Pin XLR
Wiring Diagram**

Specifications

Type:	Cardioid (unidirectional)
Polar Pattern:	Cardioid
Frequency response:	80Hz - 12kHz
Housing material:	Zinc diecast
Impedance:	600 Ohm
Sensitivity:	-70dB ±3dB
Muting:	PTT Contacts via inbuilt switch
Lead length:	2m
Gooseneck:	230mm (310mm including mic)
Baseplate dimensions:	110W x 160D x 50H mm