

# Portable Public Address

## C 7217C 150W Wireless UHF Portable PA System

Battery Replacement Guarantee\*



**3** Year Warranty



Address 500+ people

### An excellent choice for schools, places of worship & marriage celebrants.

#### RUGGED ABS CASE

All Okayo portable PA's are moulded from industrial grade ABS plastic, ensuring long life and the ability to absorb day-to-day wear and tear. Weighing under 20kgs it is truly portable in design for easy movement around school campuses or function centres. Sets up in seconds for instant use!

#### DUAL CHANNEL WIRELESS MIC RECEIVER

Supplied pre-fitted with dual channel wireless microphone receiver allowing two transmitters to be used simultaneously. 96 channels are provided for easy selection of an interference free frequency. Each channel level control can be adjusted individually.

#### OKAYO WIRELESS LINK (OPTIONAL)

All Okayo systems can be fitted with a wireless link transmitter which allows you to build an array of "linked" Okayo portable PA's all playing the same audio which is transmitted from a master unit. This allows you to scale up the Okayo system to address larger events of 2000+ people.

#### SUPERB VOCAL & MUSIC REPRODUCTION

Most PA units available on the market are tuned to high SPL music output, making them unsuitable for vocal applications. Okayo PA's offer the added flexibility of superb performance for both vocal and music reproduction.

#### HIGH EFFICIENCY AMPLIFIER & SPEAKER

High efficiency amplifier design for longer run time from batteries. It is equipped with balanced or unbalanced wired microphone inputs, plus line in and line out RCA connection. The two way speaker system consists of an 8 inch woofer and high frequency horn which has been chosen to provide crystal clear vocal performance.

#### \*BATTERY REPLACEMENT GUARANTEE

For added peace of mind Okayo offers your first replacement battery free of charge over the lifetime of your portable PA system. This is a free service provided, Altronics. Conditions apply.

**Features:** • Dual channel 96 frequency wireless UHF receiver • Bluetooth wireless audio streaming in-built • Truly portable design • Battery level indicator • Compact design sets up in just seconds • Rugged heavy duty ABS cabinet • 'Luggage' type trolley wheels • In-built extendible handle • High performance 150W max (120W RMS) amplifier • Built in backup battery • Provision for additional radio microphone receiver (520-544MHz) • Suitable for desk or speaker stand mounting • Optional wireless link for cable free transmission to additional systems • RCA line input/output • Two wired microphone inputs • 240V AC mains or battery operation

## C 7217C 150W Wireless UHF Portable PA System

### System Add Ons



#### Handheld Transmitters.

**C 7193C** With Condenser Insert.

**C 7192C** With Dynamic Insert.

- Exceptional performance
- Textured body
- Requires 2 x AA batteries, either alkaline (14 hour use) or rechargeable (11 hrs use).



#### C 7195C Beltpack Transmitter.

- Compact & lightweight with metal housing
- Fitted with 3 pin mini XLR socket
- On / Off / Mute switch
- Requires 2 x AA batteries, either alkaline (14 hour use) or NiMH rechargeable (11 hrs use).



#### C 7191 DVD Player Module

May be added for DVD & CD SD card & USB playback. Front panel features a composite video output for direct connection to a TV.



#### C 7187C Dual Channel UHF Receiver Module

Adds support for 2 more wireless microphones to any model. Maximum of 2 modules per portable PA.



#### C 7186 Protective Cover

Features left and right side pockets for Handheld microphones and a velcro cover for the mains lead input. Also has a Full zip cover for the rear panel controls.



#### C 7189C Wireless Link Transmitter

Turns a PA into a 'Master' unit allowing signals to be transmitted to 'Slave' PA units without the need for cabling. Range 70m.

### C 7217C Specifications:

Output Power (Max)	150W
Output Power (RMS)	120W
UHF Receiver	PLL synthesised control, 520-544MHz (96 Channels)
Freq. Response	20Hz - 20kHz
Mid Bass Driver	10" Woofer
Tweeter	1" Tweeter
Operating Life	Up to 6 hours (fully charged)
Charge Time	6 to 8 hours
Battery	Two 12V 4.5Ah SLA
Controls	Master volume, treble, bass; line, aux, mic 1 & mic 2 volume
Inputs	XLR 3 pin, 6.35mm TRS, stereo RCA, 3.5mm stereo
Outputs	Stereo RCA line out, 3.5mm TRS line out
Optional Modules	C 7187C Dual UHF Receiver, C 7189C Wireless Link, C 7191 DVD Player
Expansion Slots	Two (UHF slot, wireless link or CD/DVD player)
Dimensions	310D x 360W x 580Hmm
Weight	19.5kg

### Transmitter Specifications:

MODEL	C 7192C	C 7193C	C 7195C
Mic Insert	Dynamic	Condenser	None
Plug In Mics	-	-	C 7197A Lapel Mic, C 7198A Headset Mic
RF Output	10mW		
Frequency Band	PLL synthesised control, 520-544MHz (96 channels)		
Audio Input	None	None	Mini 3 Pin XLR
AF Controls	Hi/lo/mute switch		Mute switch, hi/mid/lo switch
Batteries	1.2V NiMH rechargeable x 2 or 1.5V Alkaline x 2		
Operating Life	11 hrs (NiMH) or 14 hrs (Alkaline)		
Operating Distance	Up to 70m		
Dimensions	46Ø x 264mm	46Ø x 264mm	88H x 64W x 24mm
Weight	280g	280g	170g

Available From: