

FLEX SPEAKER SERIES

FLEX 15, FLEX 30, FLEX 50

It's all in the name.....

The FLEX series of wall mount speakers are specifically designed for both indoor or outdoor commercial sound reproduction applications. Rated IP 65 with powder coated aluminium grills and stainless steel fasteners the FLEX speaker series provides the ultimate flexible solution you've been waiting for. With a smart pan and tilt bracketing system, allowing both wall or celling mounting these superb sounding speaker products are suggested for the following uses: Classrooms, Places of worship, Gymnasiums, Changing rooms, Restaurants, Bars, Beer Gardens, Swimming pools, Outdoor dining plus many more indoor or outdoor applications.





- Suitable for indoor and outdoor installations
- Weather IP65 Rated
- Powder coated aluminium grill
- Pan and tilt bracket system
- Wall or ceiling mountable
- High and Low Impedance operation
- Superb sonic performance
- Sold as pairs in white or black

Specifications

| | FLEX 15 | FLEX 30 | FLEX 50 |
|----------------------------------|---------------------------------|-------------------------------------|------------------------------|
| Rated IP65 | YES | YES | YES |
| Impedance 100v Bypass | 8 Ω | 8 Ω | 8 Ω |
| 100V Tappings Watts | 15, 7.5, 3.75, 1.87 | 30, 15, 7.5, 3.75 | 50, 25, 12.5, 6.25 |
| 70V Tappings Watts | 7.5, 3.75, 1.87, 0.93 | 15, 7.5, 3.75, 1.87 | 25, 12.5, 6.25, 3.12 |
| Max Power @ 8 Ω / RMS | 30 Watts | 40 Watts | 50 Watts |
| Sensitivity 1W/1M | 88dB | 89dB | 90dB |
| Calculated SPL RMS PEAK | 100dB 106dB | 105dB 111dB | 107dB 113dB |
| Dispersion -6 dB Points H x V | 60° x 60° | 90° x 60° | 90° x 60° |
| Frequency Response | 100-20KHz | 80-20KHz | 50-20KHz |
| Speaker Drivers | 4 Inch woofer 1 Inch tweeter | 5 1/4 Inch woofer 1 Inch tweeter | 6 ½ woofer 1 Inch tweeter |
| Product Dimensions W x D x H mm | 123 x 121 x 196 | 159 x 152 x 252 | 191 x 182 x 304 |
| Shipping Dimensions W x D x H mm | 330 x 154 x 217 | 420 x 195 x 275 | 502 x 233 x 329 |
| Shipping Weight Kg | 4.0 | 5.5 | 7.3 |

