

DICENTIS Stem Microphone

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Uni-directional microphone on adjustable stem
- ▶ Built-in pop and windshield
- ▶ Low susceptible for mobile phones
- ▶ For acoustical challenging rooms
- ▶ For locations where people want to speak standing upright

The innovative, stylish and ergonomically designed microphone with adjustable stem has a uni-directional response for optimum performance, even in noisy conditions or acoustical challenging rooms. It has low susceptibility to interference from mobile phones. For ease of use, the stem microphone is available in two lengths.

Functions


Controls and Indicators

- Red or green illuminator. Red indicates microphone active, green indicates request for speech accepted.



Interconnections

- Connector to plug and fasten the microphone.

Installation/configuration notes



Frequency response (Opening angle: 0, 90 and 180 degrees)



Polar diagram (measured with pink noise)

Technical specifications

Electrical

Power supply	5 VDC
Power consumption	0.1 W

Bandwidth	125 Hz - 15 kHz
Dynamic range	>100 dB
Nominal input	85 dB SPL
Maximum input	115 dB SPL
Equivalent noise	15 dB SPL

Mechanical

Mounting	Plug and fasten into DICENTIS device and DICENTIS Wireless Devices.
Length: DCNM-MICS (without connector) DCNM-MICL (without connector)	310 mm (12.21 in) 480 mm (19.90 in)
Connector	77.15 x 60.47 mm (3.40 x 2.38 in)
Weight: DCNM-MICS DCNM-MICL	91 g (0.20 lb) 108 g (0.24 lb)
Color: DCNM-MICS / DCNM-MICL	Traffic black RAL 9017 Pearl light grey RAL 9022

Environmental

Operating temperature	0 °C to +45 °C (32 °F to +113 °F)
Storage and transport temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Relative humidity	< 95 %, > 5%

Ordering information

DCNM-MICS Microphone with short stem

DICENTIS short stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICS**

DCNM-MICL Microphone with long stem

DICENTIS long stem microphone for the DICENTIS Conference System or DICENTIS Wireless Conference System.

Order number **DCNM-MICL**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia