Product Guide

A 4906 Mic/Line/100V Input to Line & 24V Switched Output



A 4906 Mic/Line/100V Input to Line & 24V Switched Output





Overview

The A 4906 is a versatile unit which accepts either a line level signal, balanced microphone signal or 100V input signal. The output signal is a line level signal suitable for feeding into an amplifier. Phantom power is available to the microphone input, and a VOX circuit, with adjustable sensitivity is used to trigger output relays.

Key Features

- ✓ Australian made
- ✓ 10 year manufacturer warranty with local product support
- ✓ Mic, line or 100V input level.
- ✓ Line level output.

Ph: 1300 780 999

- ✓ Phantom power to Mic Input (12V DC).
- ✓ Controls for master volume and VOX sensitivity.
- ✓ VOX operated relay outputs.
- ✓ 24VDC switched output. (120mA Max).

About Redback® Public Address Products

Redback® products are proudly designed, engineered and manufactured in Australia.

Fax: 1300 790 999

Internet: www.altronics.com.au

Each unit is covered by a comprehensive 10 year parts and labour warranty. Redback® offers rock solid reliability from over 30 years experience in the commercial sound industry. Redback® offer locally available servicing and parts, plus the ability to offer feedback direct to the manufacturer.

Product Guide

A 4906 Mic/Line/100V Input to Line & 24V Switched Output



Front Panel



Rear Panel



- 1 100V Line input
- 2 Stereo RCA auxillary line input
- 3 Output Volume control
- 4 XLR 3 pin microphone input
- 5 24V Relay contacts
- 6 VOX Sensitivity adjustment
- 7 Vox Active LED indicator
- 8 Stereo RCA line output
- 9 LED power indicator
- 10 24V DC power input socket

Specifications

| Electrical | |
|---------------------|----------------------------|
| Power: | 24V DC Input (2.1mm) |
| Max current draw: | 40mA @ 24V |
| Frequency response: | 30Hz to 10KHz (±0.5dB) |
| Noise: | > -50dB |
| Controls: | Master, Mic and Aux volume |
| Weight: | ≈ 240gm |
| Dimensions: | ≈ 133W x 65D x 44H mm |
| Colour: | Black |

Connections

| Input | Balanced / Unbalanced |
|---------|--|
| | Stereo RCA auxiliary input 3 Pin XLR microphone input |
| Outputs | Balanced |
| | 3 Pin XLR low or high level output |

